



NOTE :- DIMENSIONS IN mm

DRAWING NUMBER 007 037 298

**FITTING DETAILS**

Weight	3kg	Watertight To	0.4 bar
Voltage	115V or 220V (Lamp)	Cable Entry	No. 3 Gland
Frequency		Method of Mounting	Vertical
Rating	40W	Maximum Cable Size	16mm diameter
PF	Unity	EMC	None
Magnetic Rating		Lamps (Filament)	40W

**COMPONENT DETAILS**

COMPONENT	QTY	NSN	CLASS GROUP	REMARKS
* Lamp (Cap Type) 120V, 60W	1	6240-99-996-2364	0584	
* Lamp (Cap Type) 220V, 60W	1	6240-99-996-4555	0584	Def Stan 62-6/1
Gland Packing Nut	2	5975-99-900-4465	0559	DGS 1535
Well Glass – Type 'C'	1	6210-99-523-5974	0581	007 037 298
Light Shield	1	6260-99-477-3319	0581	007 037 298

\* To be ordered separately

**GENERAL NOTES**

1. Flight Deck lighting.
2. Helicopter Landing areas.
3. 'Looping-in' provided.
4. 40W lamp is acceptable for general use NSN 6240-99-996-2363/0584. This prevents overloading of dimmer when 15 or more lights are used.

**HAZARDOUS ITEM** – None

**Light horizon bar –  
6210-99-522-8493 – Mod 0 CL/GP 0581**