



OTE:- DIMENSIONS IN mm

DRAWING NUMBER 007 514 078

**FITTING DETAILS**

Weight	3.4kg	Watertight To	None
Voltage	115V ac	Cable Entry	Tension Grommet
Frequency	60Hz	Method of Mounting	See Figure
Rating	72VA	Maximum Cable Size	6mm diameter
PF	0.5	EMC	See EMC 19/17/83
Magnetic Rating	'A' Cert.	Lamps (Fluorescent)	8W

**COMPONENT DETAILS**

COMPONENT	QTY	NSN	CLASS GROUP	REMARKS
* Lamp (T5) 8W	3	6240-99-996-2121	0584	Def Stan 62-6/1
Lampholder Mini Bi-Pin	6	6250-99-533-0692	0585	
* Starter Switch	3	6250-12-130-6450	0585	EFA661 007 037 457
Starter Socket	3	6250-99-539-4683	0585	
Shade	1	6210-99-522-1411	0581	
Choke	3	6250-99-763-4169	0585	
Tension Grommet	1	5325-99-580-1446	0250	
Switch D/P	1	5930-99-525-7836	0567	
Capacitor	1	5910-99-619-8726	0631	
* Red Lamp Option	3	6240-99-996-5264	0584	

\* To be ordered separately

**GENERAL NOTES**

1. Internal built-in shock mounts for lamps and control gear.
2. ON-OFF slide switch.
3. 'Looping-in' provided.
4. Internally earthed.
5. Supersedes NSN 6210-99-522-1410 and NSN 6210-99-537-1143.

**HAZARDOUS ITEM** - None

**Fitting - 3 x 8W -  
6210-99-531-6502 - Mod 2 CL/GP 0581**