



DRAWING NUMBER 007 514 772

### FITTING DETAILS

Weight	1kg	Watertight To	None
Voltage	115V ac	Cable Entry	Grommets
Frequency	60Hz	Method of Mounting	See Figure
Rating	24VA	Maximum Cable Size	6mm diameter
PF	0.5	EMC	Cert. No. C18/10
Magnetic Rating	'A' Cert.	Lamps (Fluorescent)	8W

### COMPONENT DETAILS

COMPONENT	QTY	NSN	CLASS GROUP	REMARKS
* Lamp (T5) 8W	1	6240-99-996-2121	0584	Def Stan 62-6/1
Lampholder Mini Bi-Pin	2	6250-99-533-0692	0585	
Choke	1	6250-99-763-4169	0585	
* Starter Switch	1	6250-12-130-6450	0585	
Starter Socket	1	6250-99-533-0693	0585	
Grommet	4	5325-99-948-3758	0250	Def Stan 53-13
Shade, Opal 040	1	6210-99-531-1627	0581	DEE 99462
* Lamp, Red	1	6240-99-996-5264	0584	
Capacitor	1	5910-99-619-8726	0631	

\* To be ordered separately

### GENERAL NOTES

'Looping in' provided.

Earth terminal fitted.

Polycarbonate shade 6230-99-786-2035 required when fitting used for serveries.

Use:-

1. Red Lighting with standard Opal shade (Opal 040). Alternative Opal 028 shade NSN 6210-99-786-2036, available to reduce light output for dark adaptation.
2. Mirror lights over washbasins (unswitched items only).
3. Not suitable for Officers' Bunk use; use 0581/533-0287.
4. Not suitable for use as desk light; use 0581/533-0287.
5. Supersedes Item 6210-99-525-7136.
6. Proprietary to Westair.

HAZARDOUS ITEM – None

**MCMV Amenity light – 1 × 8W –  
6210-99-531-6511 – Mod 1 CL/GP 0581**