



NOTE DIMENSIONS IN mm

DRAWING NUMBER 007 514 770

FITTING DETAILS

Weight	1kg	Watertight To	None
Voltage	115V ac	Cable Entry	Grommet
Frequency	60Hz	Method of Mounting	See Figure
Rating	21VA	Maximum Cable Size	6mm diameter
PF	0.5	EMC	See EMC 19/24/83
Magnetic Rating	'A' Cert.	Lamps (Fluorescent)	8W

COMPONENT DETAILS

COMPONENT	QTY	NSN	CLASS GROUP	REMARKS
* Lamp (T5) 8W	1	6240-99-996-2121	0584	Def Stan 62-6/1
Lampholder Mini Bi-Pin	2	6250-99-533-0692	0585	
Choke	1	6250-99-763-4169	0585	
* Starter Switch	1	6250-12-130-6450	0585	
Starter Socket	1	6250-99-533-0693	0585	
Grommet	4	5325-99-948-3758	0250	Def Stan 53-13
Switch	1	5930-99-525-7836	0567	
Capacitor	1	5910-99-619-8726	0631	
Shade	1	6210-99-531-1627	0581	Dee 99462
* Desk Shade	1	6230-99-786-2034	0581	007 037 489
* Red Lamp Option	1	6240-99-996-5264	0584	
* To be ordered separately				

GENERAL NOTES

1. Suitable for MCMV use.
2. Officers' bunklight or desk light only – not to be used as mirror light (use 0581/531-6511).
3. 'Looping-in' provided.
4. Earth terminal fitted.
5. Desk shade required when fitting used as a desk light.
6. Supersedes Item 6210-99-525-1270.

HAZARDOUS ITEM – None

**MCMV Fitting – 1 × 8W – 6210-99-533-0287 –
Mod 1 CL/GP 0581**