



DRAWING NUMBER 007 037 417 AND SERIES

FITTING DETAILS

Weight	2.2kg	Watertight To	0.1 bar
Voltage	115/220V ac/dc	Cable Entry	Screwed Conduit
Frequency	50/60Hz	Method of Mounting	See Figure
Rating	60W	Maximum Cable Size	
PF	Unity	EMC	
Magnetic Rating		Lamps	

COMPONENT DETAILS

COMPONENT	QTY	NSN	CLASS GROUP	REMARKS
* Key, Switch	1	5930-99-923-5433	0567	Chat SEE 179B
* Shade, Glass, Red	1	6210-99-412-8244	0581	DEE 92451
* Shade, Glass, Clear	1	6210-99-779-8859	0581	DEE 92451
Lampholder	1	6250-99-412-8499	0585	
Section Ring, Rubber	1	5530-99-924-2211	0413	007037417/019
Section Ring, 'U' Shaped	1	5530-99-924-2294	0413	007037417/020
Shield	1	5970-99-923-4556	0559	007037417/016
Mounting Plate	1	5999-99-923-4557	0559	007037419/003
Guard	1	6210-99-923-4564	0581	007037418/003
** Guard Plastic Coated Pad	1	6210-99-742-6385		007 521 063 See note

* To be ordered separately. ** NOT to be used in Magazine

GENERAL NOTES

1. Pad – Well dressed leather, cemented in.
2. Plastic guard required for use in submarine battery compartments.
3. Supersedes NSN 6210-99-923-5807.

HAZARDOUS ITEM – None

**Magazine fitting (Metric conduit) –
6210-99-765-9118 – Mod 1 CL/GP 0581**