



SHORT TYPE WATERTIGHT

NOTE - DIMENSIONS IN mm

DRAWING NUMBER CH726E

FITTING DETAILS

Weight	0.68kg	Watertight To	Watertight
Voltage	115/220V ac/dc	Cable Entry	Looping-in base
Frequency	60Hz	Method of Mounting	Vertical
Rating	60W or 40W	Maximum Cable Size	8mm diameter
PF	Unity	EMC	None
Magnetic Rating	'A' Cert.	Lamps (Filament)	60W or 40W

COMPONENT DETAILS

COMPONENT	QTY	NSN	CLASS GROUP	REMARKS
* Lamp (BC) 115V - 60W	1	6240-99-996-2364	0584	Def Stan 62-6/1
OR				
* Lamp (BC) 220V - 60W	1	6240-99-996-4555	0584	Def Stan 62-6/1
* Globe (Clear)	1	6210-99-531-2511	0581	One required to complete SEE CH 680H
* Globe (Blue)	1	6210-99-923-5731	0581	
* Globe (Green)	1	6210-99-923-5771	0581	
* Globe (Red)	1	6210-99-923-5768	0581	
For use with Clear Globe for Red Lighting				
Lamp (BC) 115V - 40W Red	1	6240-99-996-5452	0584	Def Stan 62-6/1
OR				
Lamp (BC) 220V - 40W Red	1	6240-99-996-4480		
* Rubber Gasket				AP2482
Guard Wire	1	6210-99-923-5431	0581	

* To be ordered separately

GENERAL NOTES

1. Spanner - 0274/923-5813.
2. Looping-in Base (Junction Box) NSN 5940-99-923-5728/0559.

HAZARDOUS ITEM - None

**W/T Pendant, short -
6210-99-923-5758 - Mod 0 CL/GP 0581**