



DRAWING NUMBER CH 719E

**FITTING DETAILS**

Weight	0.68kg	Watertight To	Watertight
Voltage	115/220V ac	Cable Entry	Looping-in base
Frequency	60Hz	Method of Mounting	Vertical
Rating	60W or 40W	Maximum Cable Size	8mm diameter
PF	Unity	EMC	None
Magnetic Rating	'A' Cert.	Lamps (Filament)	60W or 40W

**COMPONENT DETAILS**

COMPONENT	QTY	NSN	CLASS GROUP	REMARKS
* Lamp (BC) 115V - 60W	1	6240-99-996-2364	0584	Def Stan 62-6/1
OR				
* Lamp (BC) 220V - 60W	1	6240-99-996-4555	0584	Def Stan 62-6/1
* Globe (Clear)	1	6210-99-923-5449	0581}	Def Stan 62-6/1
* Globe (Blue)	1	6210-99-923-5731	0581}	One required
* Globe (Green)	1	6210-99-923-5771	0581}	to complete
* Globe (Red)	1	6210-99-923-5768	0581}	SEE CH 680H
For use with Clear Globe for Red Lighting				
* Lamp (BC) 115V - 40W Red	1	6240-99-996-5452	0584	Def Stan 62-6/1
OR				
* Lamp (BC) 220V - 40W Red	1	6240-99-996-4480		Def Stan 62-6/1

\* To be ordered separately

**GENERAL NOTES**

1. Spanner - 0274/923-5813.
2. Looping-in Base (Junction Box) NSN 5940-99-923-5728/0559.

**HAZARDOUS ITEM** - None

**W/T Pendant, medium -  
6210-99-923-9894 - Mod 0 CL/GP 0581**