



DRAWING NUMBER 007 037 381

**FITTING DETAILS**

Weight	14.1kg	Watertight To	60 bar
Voltage	24V ac	Cable Entry	Pressure Gland
Frequency	60Hz	Method of Mounting	See above Figure
Rating	40W	Maximum Cable Size	See DEE B87165
PF	N/A	EMC	N/A
Magnetic Rating	N/A	Lamps (Filament)	40W, 50cd

**COMPONENT DETAILS**

COMPONENT	QTY	NSN	CLASS GROUP	REMARKS
Lamp	1	6240-12-168-2921	0584	Radium Pt No. 2450C
Fresnel Lens Assy	1	6220-99-031-7116	0582	007 037 388
Light Cut-off Shield	1	6220-99-152-3455	0582	007 037 380
Lampholder	1	6250-99-853-3203	0585	007 037 396
Cable Gland	1	5975-99-522-3796		DEE B87165
'O' Ring Seal (Lens Assy)	1	5330-99-453-4489		Dowty Pt No. 100-338-1911
'O' Ring Seal (Gland)	1	5330-99-104-8955		Dowty Pt No. 100-217-1911
'O' Ring Seal (Gland)	1	5330-99-453-4483		Dowty Pt No. 100-221-1911
4-Way Plug (Lantern)	1	5935-99-972-8222	0568	
4-Way Socket (Gland)	1	5935-99-972-8188		

**GENERAL NOTES**

1. This light satisfies the requirements of the Merchant Shipping (Distress Signals and Prevention of Collisions) Regulations 1989.
2. Production Test Specification – PTS Number 16123.

**HAZARDOUS ITEM** – None

**Starboard light (single), navigation submarine –  
6220-99-349-6468 – Mod 0 CL/GP**