



DRAWING NUMBER 007 037 387

FITTING DETAILS

| | | | |
|-----------------|--------|--------------------|------------------|
| Weight | 12.7kg | Watertight To | 60 bar |
| Voltage | 24V ac | Cable Entry | Pressure Gland |
| Frequency | 60Hz | Method of Mounting | See above Figure |
| Rating | 40W | Maximum Cable Size | See DEE B87165 |
| PF | N/A | EMC | N/A |
| Magnetic Rating | N/A | Lamps (Filament) | 40W, 50cd |

COMPONENT DETAILS

| COMPONENT | QTY | NSN | CLASS GROUP | REMARKS |
|---------------------------|-----|------------------|-------------|---------------------------|
| Lamp | 1 | 6240-12-168-2921 | 0584 | Radium Pt No. 2450C |
| Fresnel Lens Assy | 1 | 6220-99-570-0881 | 0582 | 007 037 395 |
| Lampholder | 1 | 6250-99-853-3203 | 0585 | 007 037 396 |
| Cable Gland | 1 | 5975-99-522-3796 | | DEE B87165 |
| 'O' Ring Seal (Lens Assy) | 1 | 5330-99-453-4489 | | Dowty Pt No. 100-338-1911 |
| 'O' Ring Seal (Gland) | 1 | 5330-99-104-8955 | | Dowty Pt No. 100-217-1911 |
| 'O' Ring Seal (Gland) | 1 | 5330-99-453-4483 | | Dowty Pt No. 100-221-1911 |
| 4-Way Plug (Lantern) | 1 | 5935-99-972-8222 | 0568 | |
| 4-Way Socket (Gland) | 1 | 5935-99-972-8188 | | |

GENERAL NOTES

1. This light satisfies the requirements of the Merchant Shipping (Distress Signals and Prevention of Collisions) Regulations 1989.
2. Production Test Specification – PTS Number 16123.

HAZARDOUS ITEM – None

**Anti-collision light (single), navigation submarine –
6220-99-398-6369 – Mod 0 CL/GP 0582**