



DRAWING NUMBER 007 037 382

#### FITTING DETAILS

Weight	30.9kg	Watertight To	60 bar
Voltage	24V ac	Cable Entry	Pressure Gland
Frequency	60Hz	Method of Mounting	See above Figure
Rating	40W	Maximum Cable Size	See DEE B87165
PF	N/A	EMC	N/A
Magnetic Rating	N/A	Lamps (Filament)	40W, 50cd

#### COMPONENT DETAILS

COMPONENT	QTY	NSN	CLASS GROUP	REMARKS
Lamp	1	6240-12-168-2921	0584	Radium Pt No. 2450C
Fresnel Lens Assy	1	6220-99-024-8620	0582	007 037 390
Light Cut-off Shield	1	6220-99-215-1755	0582	007 037 391
	1	6220-99-629-9970	0582	007 037 382
Lampholder	1	6220-99-152-3455	0582	007 037 380
Cable Gland	2	6250-99-955-9264	0585	007 037 397
'O' Ring Seal (Lens Assy)	1	5975-99-522-3796		DEE B87165
'O' Ring Seal (Gland)	2	5330-99-453-4489		Dowty Pt No. 100-338-1911
'O' Ring Seal (Gland)	1	5330-99-104-8955		Dowty Pt No. 100-217-1911
'O' Ring Seal (Gland)	1	5330-99-453-4483		Dowty Pt No. 100-221-1911
4-Way Plug (Lantern)	1	5935-99-972-8222	0568	
4-Way Socket (Gland)	1	5935-99-972-8188		

#### GENERAL NOTES

1. This light satisfies the requirements of the Merchant Shipping (Distress Signals and Prevention of Collisions) Regulations 1989.
2. Production Test Specification – PTS Number 16123.

HAZARDOUS ITEM – None

**Port light (double fitting), navigation submarine –  
6220-99-427-5732 – Mod 0 CL/GP 0582**