



FITTING DETAILS

Weight (approx) 4.5kg
 Voltage 110/220V ac
 Frequency 60Hz
 Rating 85W
 PF Unity
 Magnetic Rating 'A' Cert.

Watertight To Cable Entry
 Method of Mounting
 Maximum Cable Size
 EMC
 Lamps

See General Notes
 Gland
 See Figure
 7-15mm diameter

See General Notes and
 Component Details

COMPONENT DETAILS

COMPONENT	QTY	NSN	CLASS GROUP	REMARKS
Lampholder Installation Plate	1	6230-99-539-7048	0583	
Gland	1	5975-99-539-7049	0559	
* Gland Adaptor	1	6220-99-541-1939	0582	007033550
* Lamp 110V, 35cd, 55W	1	6240-99-539-3397	0584	006050817 (See General Notes)
* Lamp 220V, 35cd, 55W	1	6240-99-539-3398	0584	
* Lamp 110V, 65cd, 80W	1	6240-99-539-3389	0584	
* Lamp 220V, 65cd, 85W	1	6240-99-539-3390	0584	
* Lamp, Emergency, 24V, 35cd, 55W	1	6240-99-539-3396	0584	
* Lamp, Emergency, 24V, 50cd, 48W	1	6240-99-539-3391	0584	Vessels under 50 metres Vessels over 50 metres

* To be ordered separately

GENERAL NOTES

1. For use in vessels above 20 metres length.
2. Dust proof and jet proof to IP 56 class.
3. 35 candela (cd) lamps are for use in vessels 20-50 metres length.
4. 65 candela (cd) lamps are for use in vessels over 50 metres in length.
5. Suitable for use in Hunt Class MCMVs.

HAZARDOUS ITEM - None

**Lantern, sidelight (starboard) -
 6220-99-539-4336 - Mod 0 CL/GP 0582**