



FITTING DETAILS

Weight	(approx) 4.5kg	Watertight To	See General Notes
Voltage	110/220V ac	Cable Entry	Gland
Frequency	60Hz	Method of Mounting	See Figure
Rating	85W	Maximum Cable Size	7-15mm diameter
PF	Unity	EMC	
Magnetic Rating	'A' Cert.	Lamps	See General Notes and Component Details

COMPONENT DETAILS

COMPONENT	QTY	NSN	CLASS GROUP	REMARKS
Lampholder Installation Plate	1	6230-99-539-7048	0583	
Gland	1	5975-99-539-7049	0559	
* Gland Adaptor	1	6220-99-541-1939	0582	007033550
* Lamp 110V, 35cd, 55W	1	6240-99-539-3397	0584	006050817 (See General Notes)
* Lamp 220V, 35cd, 55W	1	6240-99-539-3398	0584	
* Lamp 110V, 65cd, 80W	1	6240-99-539-3389	0584	
* Lamp 220V, 65cd, 85W	1	6240-99-539-3390	0584	Vessels under 50 metres Vessels over 50 metres
* Lamp, Emergency, 24V, 35cd, 55W	1	6240-99-539-3396	0584	
* Lamp, Emergency, 24V, 50cd, 48W	1	6240-99-539-3391	0584	

* To be ordered separately

GENERAL NOTES

1. For use in vessels above 20 metres length.
2. Dust proof and jet proof to IP 56 class.
3. 35 candela (cd) lamps are for use in vessels 20-50 metres length.
4. 65 candela (cd) lamps are for use in vessels over 50 metres in length.
5. Suitable for use in Hunt Class MCMVs.

HAZARDOUS ITEM – None

**Lantern, stern –
6220-99-539-4337 – Mod 0 CL/GP 0582**