



Weight (approx) 4.5kg  
 Voltage 110/220V ac  
 Frequency 60Hz  
 Rating 85W  
 PF Unity  
 Magnetic Rating 'A' Cert.

#### FITTING DETAILS

Watertight To  
 Cable Entry  
 Method of Mounting  
 Maximum Cable Size  
 EMC  
 Lamps

See General Notes  
 Gland  
 See Figure  
 7-15mm diameter

See General Notes and  
 Component Details

#### COMPONENT DETAILS

COMPONENT	QTY	NSN	CLASS GROUP	REMARKS
Lampholder Installation Plate	1	6230-99-539-7048	0583	
Gland	1	5975-99-539-7049	0559	
* Gland Adaptor	1	6220-99-541-1939	0582	007033550
* Lamp 110V, 35cd, 55W	1	6240-99-539-3397	0584	} 006050817 (See General Notes)
* Lamp 220V, 35cd, 55W	1	6240-99-539-3398	0584	
* Lamp 110V, 65cd, 80W	1	6240-99-539-3389	0584	
* Lamp 220V, 65cd, 85W	1	6240-99-539-3390	0584	

\* To be ordered separately

#### GENERAL NOTES

1. For use in vessels above 20 metres length.
2. Dust proof and jet proof to IP 56 class.
3. 35 candela (cd) lamps are for use in vessels 20-50 metres length.
4. 65 candela (cd) lamps are for use in vessels over 50 metres in length.

HAZARDOUS ITEM – None

**Lantern, towing –  
 6220-99-539-4338 – Mod 0 CL/GP 0582**