



DRAWING NUMBER 007 037 399

**FITTING DETAILS**

Weight	14.1kg	Watertight To	60 bar
Voltage	24V ac	Cable Entry	Pressure Gland
Frequency	60Hz	Method of Mounting	See above Figure
Rating	40W	Maximum Cable Size	See 007 502 132
PF	N/A	EMC	N/A
Magnetic Rating	N/A	Lamps (Filament)	40W, 50cd

**COMPONENT DETAILS**

COMPONENT	QTY	NSN	CLASS GROUP	REMARKS
Lamp	1	6240-12-168-2921	0584	Radium Pt No. 2450C
Fresnel Lens Assy	1	6220-99-031-7116	0582	007 037 388
Light Cut-off Shield	1	6220-99-152-3455	0582	007 037 380
Lampholder	1	6250-99-061-1888		007 037 405
Cable Gland	1	5975-99-521-3364	0559	DEE B85031
'O' Ring Seal (Lens Assy)	1	5330-99-453-4489		Dowty Pt No. 100-338-1911
'O' Ring Seal (Gland)	1	5330-99-104-8955		Dowty Pt No. 100-217-1911
'O' Ring Seal (Gland)	1	5330-99-453-4483		Dowty Pt No. 100-221-1911
2-Way Plug (Lantern)	1	5935-99-972-8221	0568	
2-Way Socket (Gland)	1	5935-99-972-8187		

**GENERAL NOTES**

1. This light satisfies the requirements of the Merchant Shipping (Distress Signals and Prevention of Collisions) Regulations 1989.
2. Production Test Specification – PTS Number 16123.

**HAZARDOUS ITEM** – None

**Starboard light (single), navigation submarine –  
6220-99-867-7321 – Mod 0 CL/GP 0582**