



DRAWING NUMBER 007 037 380

FITTING DETAILS

Weight	30.9kg	Watertight To	60 bar
Voltage	24V ac	Cable Entry	Pressure Gland
Frequency	60Hz	Method of Mounting	See above Figure
Rating	40W	Maximum Cable Size	See DEE B87165
PF	N/A	EMC	N/A
Magnetic Rating	N/A	Lamps (Filament)	40W, 50cd

COMPONENT DETAILS

COMPONENT	QTY	NSN	CLASS GROUP	REMARKS
Lamp	1	6240-12-168-2921	0584	Radium Pt No. 2450C
Fresnel Lens Assy	1	6220-99-031-7116	0582	007 037 388
Light Cut-off Shield	1	6220-99-215-9599	0582	007 037 389
	1	6220-99-152-3455	0582	007 037 380
Lampholder	1	6220-99-629-9970	0582	007 037 382
Cable Gland	2	6250-99-955-9264	0585	007 037 397
'O' Ring Seal (Lens Assy)	1	5975-99-522-3796		DEE B87165
'O' Ring Seal (Gland)	2	5330-99-453-4489		Dowty Pt No. 100-338-1911
'O' Ring Seal (Gland)	1	5330-99-104-8955		Dowty Pt No. 100-217-1911
4-Way Plug (Lantern)	1	5330-99-453-4483		Dowty Pt No. 100-221-1911
4-Way Socket (Gland)	1	5935-99-972-8222	0568	
		5935-99-972-8188		

GENERAL NOTES

1. This light satisfies the requirements of the Merchant Shipping (Distress Signals and Prevention of Collisions) Regulations 1989.
2. Production Test Specification – PTS Number 16123.

HAZARDOUS ITEM – None

**Starboard light (double fitting), navigation submarine –
6220-99-932-6470 – Mod 0 CL/GP 0582**