



NOTE - DIMENSIONS IN mm

DRAWING NUMBER DEE 96998

FITTING DETAILS

Weight	1kg	Watertight To	None
Voltage	115V ac	Cable Entry	Grommets
Frequency	60Hz	Method of Mounting	See Figure
Rating	18VA	Maximum Cable Size	6mm diameter
PF	0.5	EMC	See EMC 19/15/83
Magnetic Rating	'C' Cert.	Lamps (Fluorescent)	4W

COMPONENT DETAILS

COMPONENT	QTY	NSN	CLASS GROUP	REMARKS
* Lamp (T5) 4W	1	6240-99-996-5259	0584	Def Stan 62-6/1
Lampholder Mini Bi-Pin	2	6250-99-533-0692	0585	
Choke	1	6250-99-763-4169	0585	
* Starter Switch	1	6250-12-130-6450	0585	
Starter Socket	1	6250-99-533-0693	0585	
Grommet	2	5325-99-942-3420	0250	
Switch D/P	1	5930-99-525-7836	0567	
Capacitor	1	5910-99-619-8726	0631	
* Red Lamp Option	1	6240-99-996-2235	0584	
Cover Assy including Diffuser	1	6210-99-537-5646	0581	Steel 007 516 236

* To be ordered separately

GENERAL NOTES

1. Inner rotating light cut-off shield.
2. ON-OFF slide switch.
3. Internal built-in shock mounts for lamp and control gear.
4. Bunklight.
5. Internally earthed.
6. This fitting when fitted with a red lamp supersedes fitting 6230-99-529-3719.

HAZARDOUS ITEM - None

**Bunk light - 1 x 4W -
6230-99-529-3717 - Mod 1 CL/GP 0583**