



DRAWING NUMBER 007 040 316

#### FITTING DETAILS

Weight	1.63kg	Watertight To	None
Voltage	115V ac	Cable Entry	Grommet
Frequency	60Hz	Method of Mounting	See Figure
Rating	45VA	Maximum Cable Size	6mm diameter
PF	0.5	EMC	None
Magnetic Rating	'C' Cert.	Lamps (Fluorescent)	6W

#### COMPONENT DETAILS

COMPONENT	QTY	NSN	CLASS GROUP	REMARKS
* Lamp (T5) 6W	2	6240-99-996-2240	0584	Def Stan 62-6/1
Lampholder Mini Bi-Pin	4	6250-99-533-0692	0585	
Choke	2	6250-99-763-4169	0585	
* Starter Switch	2	6250-12-130-6450	0585	
Starter Socket	2	6250-99-520-2204	0585	
Grommet	2	5325-99-948-3758	0250	Def Stan 53-13
Shade	1	6220-99-773-7806	0581	007 503 296
* Red Lamp Option	2	6240-99-996-2252	0584	
* Shade Polycarbonate	1	6210-99-746-0942	0581	007 513 839

\* To be ordered separately

#### GENERAL NOTES

1. 'Looping in' provided.
2. Internally earthed.
3. Polycarbonate shade required when fitting used for serveries.
4. Supersedes 6210-99-525-2308.

HAZARDOUS ITEM – None

**Amenity – 2 × 6W –  
6230-99-745-4353 – Mod 0 CL/GP 0583**